	June 1, 2003	FP0-008
FIRE PREVENTION STANDARDS	APPROVED;	REVISED: 8/12/2024
	TITLE:	

## **PURPOSE**

The purpose of this standard is to provide minimum bridge specifications that require fire apparatus access within the County of Santa Cruz. When a bridge is required to be used as part of a fire apparatus access road, it shall be constructed and maintained in accordance with nationally recognized standards.


## **SCOPE**

Bridge load limit signs and current certification by a licensed engineer shall be provided for all new and existing bridges located within the County of Santa Cruz.

## **REQUIREMENTS**

- 1. Private bridge re-certification
  - A. Private bridges shall be recertified by a licensed engineer in accordance with the current version of the California Fire Code with local amendments.
  - B. Certified/recertified date shall be posted on the Weight Limit sign
- 2. Minimum sign specifications are as follows:
  - A. Signs shall be posted at both entrances to all private bridges.
  - B. Signs shall be a minimum of 18" x 24", 18-gauge steel sign white in color with black lettering.
  - C. Letters shall be a minimum of 3-1/2 inches in height with 3/8-inch stroke.
  - D. When bridge entrances are not lit, a reflective sign may be required
  - E. The bridge weight limit, as determined by a State of California Registered Civil or structural Engineer, shall appear above the words "TONS".
  - F. The sign will state:

## (example)



WEIGHT LIMIT

\*Series 2000 Standard Alphabets.
\*\*See page 6-4 for design
\*\*\*See page 6-5 for design
\*\*\*See page 6-6 for design

	A	В	C	D	E	F	G	Н	J	K	L	M
C	24	36	.375	.625	3.25	3.5 E	3	3.5 D	9.465	6.403	10.375	7
	30	42	.5	.75	3.75	4.5 E	3	4.5 D	12.016	8.192	13.188	9
	36	48	.625	.875	5	5 E	3.25	5 D	13.350	9.099	15	10
	48	60	.75	1.25	6	6 E	4.5	6 D	16.02	10.918	19	12

N	P	Q	R	S
VAR	11	12.813	3.5	1.5
VAR	13.438	16.438	4.5	1.875
VAR	15.438	18.375	5	2.25
VAR	19.688	22	6	3

COLORS: LEGEND — BLACK BACKGROUND— WHITE (RETROREFLECTIVE)

1-162